



TECHNICAL REQUIREMENTS

DESIGN AND MANUFACTURE: BS 1873

FACE TO FACE : ASME B16.10

FLANGED ENDS :ASME B16.5

TEST AND INSPECTION : API 598

20	NUT	ASTM A194 8
19	BOLT	ASTM A193 B8
18	STEM NUT	BRASS
17	SCREW	A29 1035
16	GASKET	A276 410
15	HANDWHEEL	KT330-08
14	NUT	ASTM A194 8
13	EYE NUT	ASTM A194 8
12	EYE BOLT	ASTM 193 B8
11	GLAND FLANGE	ASTM A351 CF8M
10	GLAND	A276 316
9	PIN	A276 316
8	PACKING	GRAPHITE
7	BACKSEAT	A276 316
6	BONNET	ASTM A351 CF8M
5	GASKET	316+GRAPHITE
4	DISC COVER	A276 316
3	STEM	ASTM A182 F316
2	DISC	A182 F316L +STL6
1	BODY	ASTM A351 CF8M
NO.	PARTS NAME	MATERIAL

3"								
NPS	d	L	D	D1	D2	B	T	N-φP

PERFORMANCE LIST							
CLASS			lb				
TEST	SHELL		MP <sub>a</sub>	MARK	QUANTITY	SIGN	DATE
	SEAT / BACK SEAT			DESIGN	STANDARDIZATION		
	AIR			CHECK	APPROVE		
MAX. TEMP.			°C	AUDIT			
MEDIUM: WATER,OIL, GAS				PROCESS	DATE		

Wenzhou Sn-Joe Flow Tech Equipment Co., Ltd.

MARK	WEIGHT	PROPERTION

GLOBE VALVE  
J41Y-600LB-00