

Model	REM-500		
Rated power	500W		
Peak power	1000W		
Input voltage	DC12V	DC24V	DC48V
Output voltage	100VAC or 110VAC or 120VAC or 220VAC or 230VAC or 240VAC±5%		
Unload current less than	0.3A	0.1A	0.1A
Output frequency	50Hz±0.5Hz or 60Hz±0.5Hz		
Output waveform	Modified Sine Wave		
USB port	5V 1A		
Max. efficiency	90%		
Input voltage range	10-15.5V	20-31V	40-61V
Low voltage alarm	10.5±0.5V	21±0.5V	42±1V
Low voltage protection	10±0.5V	20±0.5V	40±15V
Over voltage protection	15.5±0.5V	31±0.5V	61±1V
Low voltage recover	12.3±0.5V	24±0.5V	48±1V
Over voltage recover	14.8V±0.5V	29.5V±0.5V	59V±1V
Working temperature	.-10°- +50°		
Storage temperature	.-30°-+ 70°		
(LxWxH) Dimension(mm)	185*115*60		
Packing(mm)	265x145x70		
Net./gross weight(g)	940/1040		
QTY/Cth	10Pcs		
Meas.Ctn(mm)	635x330x535		
Warranty	2 years		
Cooling method	Intelligent air cooling		